

Wet/Wet Differential Pressure Transmitter

Introduction

The series 629 Differential Pressure Transmitter monitor differential pressure of air and compatible gases & liquids with 0.5% accuracy.

Specifications

Service:	compatible gases & liquids
Accuracy:	±0.5% FS
Output:	4-20 mA (optional 0-5, 0-10 VDC)
Response Time:	50 mS
Display:	Optional 4.5 digit Red LED
Connections:	¼" female NPT
Power Req:	13-30 VDC Loop Power

Applications

Measure Differential Pressure across:

- Flow Elements
- Heat exchangers
- Filters
- Pumps
- Coils



Options

- 3-way valve manifold
- 4.5 Digit LED Display



Models Available

Code	Range
IPX-629*02	0/10 psid
IPX-629*03	0/25 psid
IPX-629*04	0/50 psid
IPX-629*05	0/100 psid
-LED	Add this to above code for LED display
-3V	Add this to above code for 3-way valve package

Postal Address
Homersham Ltd
PO Box 280
Christchurch 8140
NEW ZEALAND

Phone: 03 3588309
Phone: 0800 659888

Website: www.homershams.co.nz

Delivery Address
Homersham Ltd
3 Homersham Place
Burnside
Christchurch 8053
NEW ZEALAND

Fax: 03 3582516
Fax: 0800 659777

E-mail: info@homershams.co.nz