

Pressure Gauges - General Purpose 100mm

Introduction

These New Zealand made gauges have a variety of uses including Gas and Liquid service up to 50 °C.

Specifications

Case	Glass Filled Nylon
Bourdon	Copper alloy
Dial	Dual Scale kPa & psi
Accuracy	± 1.0 % FS
Connection	3/8 BSP Parallel 1/2 BSP Parallel (>6000kPa) Brass Bottom Entry

Features

- Manufactured in accordance with general specifications laid down in B.S.1780 Part 2 1971. (N.Z.S. 1084)
- % Accuracy
- Rugged construction
- Wall mounting



Models Available

Code	kPa	psi
3400HWD01	-100/0	-30 in Hg/0
3400HWD18	-100/150	-30 in Hg/21
3400HWD19	-100/300	-30 in Hg/43
3400HWD20	-100/500	-30 in Hg/72
3400HWD21	-100/900	-30 in Hg/130
3400HWD22	-100/1500	-30 in Hg/217
3400HWD23	-100/2400	-30 in Hg/348
3400HWD02	0/100	0/15
3400HWD03	0/160	0/23
3400HWD04	0/250	0/36
3400HWD05	0/400	0/60

Code	kPa	psi
3400HWD05	0/400	0/60
3400HWD06	0/600	0/87
3400HWD07	0/1000	0/145
3400HWD08	0/1600	0/232
3400HWD09	0/2500	0/362
3400HWD10	0/4000	0/580
3400HWD11	0/6000	0/870
3400HWD12	0/10000	0/1450
3400HWD13	0/16000	0/2321
3400HWD14	0/25000	0/3626
3400HWD15	0/40000	0/5802

Postal Address
Homersham Ltd
P.O. Box 280
CHRISTCHURCH 8015
NEW ZEALAND

Phone: 03 3588309
Phone: 0800 659888

Website: www.homershams.co.nz

Delivery Address
Homersham Ltd
3 Homersham Place
CHRISTCHURCH 8005
NEW ZEALAND

Fax: 03 3582516
Fax: 0800 659777

E-mail: info@homershams.co.nz
Section 3



Temperature
Pressure