

Melt Pressure Transducers

Introduction

With 100% form fit and functionality at the most competitive prices, ONEhalf20 Melt Pressure Transducers and Transmitters are rapidly becoming the preferred choice of cost conscious Plastics Processors throughout the Globe. ONEhalf20 Melt Pressure Transducers and Transmitters offer high accuracy, repeatability, industry standard functionality at prices substantially below the competitors.

Specifications

Range:	0-70 bar to 0/1,000 bar (Imperial Ranges available)
Mounting:	½-20 UNF thread
Temp Limits:	Diaphragm 400 °C Electronics 120 °C
Accuracy:	General Purpose <0.5% FSO Laboratory <0.25% FSO



Options

- CT = Classic Style – Rigid Stem with 18” Flex Armour
- RT = Rigid Style – Stem only

Models Available

Code	Style	Stem Length	O/P Type	Range	Options
IPX-CT6S1MB	Classic	153mm	3.3mV/Volt	0 to 1,000 bar	
IPX-CT6S1MBTCK	Classic	153mm	3.3mV/Volt	0 to 1,000 bar	Type K T/C

The above options are stocked in Christchurch but others are available and can be quoted on request.

Cross References are available for GP50, Dynisco, Gefran and Gentran brands.

Postal Address
Homersham Ltd
P.O. Box 280
CHRISTCHURCH 8015
NEW ZEALAND

Phone: 03 3588309
Phone: 0800 659888

Website: www.homershams.co.nz

Delivery Address
Homersham Ltd
3 Homersham Place
CHRISTCHURCH 8005
NEW ZEALAND

Fax: 03 3582516
Fax: 0800 659777

E-mail: info@homershams.co.nz
Section 3



Temperature
Pressure