

## Noryl® Flow Switch – P2

### Introduction

The compact Series P2 Noryl® Flow Switch utilises a piston type design for clean water applications.

### Specifications

Temperature:	18 to 100 °C
Max Pressure:	10 bar @ 20 °C 3 bar @ 100 °C
Switch Type:	SPST NO
Switch Rating:	20 VA
Process Connection:	¼ " male NPT



### Applications

- Pure Water Equipment
- Filter life monitoring
- Heat Exchangers
- Cooling Applications

## Models Available

Code	Description	Set Point
IFS-P211	P2-11 Noryl® Flow Switch	0.05 GPM (0.189 lpm)
IFS-P212	P2-12 Noryl® Flow Switch	0.25 GPM (0.946 lpm)

**Postal Address**  
Homersham Ltd  
P.O. Box 280  
CHRISTCHURCH 8015  
NEW ZEALAND

Phone: 03 3588309  
Phone: 0800 659888

Website: [www.homershams.co.nz](http://www.homershams.co.nz)

**Delivery Address**  
Homersham Ltd  
3 Homersham Place  
CHRISTCHURCH 8005  
NEW ZEALAND

Fax: 03 3582516  
Fax: 0800 659777

E-mail: [info@homershams.co.nz](mailto:info@homershams.co.nz)  
Section 5



Temperature  
Pressure