

Kokusai Thermo-Hygrograph



Specifications

Type	Self-recording, wall mounted
Number of Pens	One red and one blue. Last for six months
Recording chart	Circular chart 165mm (6.6 inches) in diameter
Recording time	One revolution every day, eight days, or thirty-two days
Power supply	One 1.5V battery (IEC R6P, ANSI AA (The service life is one year before replacement is necessary.))
Sensors	Built in.
Temperature	Bimetal
Humidity	Nylon film
Scale ranges:	
Temperature	-10 ° C to 40 ° C or 10 ° F to 110° F
Relative Humidity	0% to 100%RH
Accuracy:	
Temperature	+ 2° C or + 4° F (Minimum scale on chart 1° C or 2° F)
Relative humidity	+ 5% RH between 30% & 90% RH (Minimum scale on chart 2%)
External Dimensions	Approximately 200mm X 200MM X 60mm
Color of cover	Green or Ice white
Weight	Approximately 650 g (1.5 lb)
Standard Accessories	30 sheets of circular recording-chart paper
	A set of disposable pen cartridges (one red, one blue)
	One battery (IEC R6P, ANSI AA)
	One mounting wood screw

Postal Address
Homersham Ltd
P.O. Box 280
CHRISTCHURCH 8015
NEW ZEALAND

Phone: 03 3588309
Phone: 0800 659888

Website: www.homershams.co.nz

Delivery Address
Homersham Ltd
3 Homersham Place
CHRISTCHURCH 8005
NEW ZEALAND

Fax: 03 3582516
Fax: 0800 659777

E-mail: info@homershams.co.nz
Section 6



Temperature
Pressure